
F/NIPPLE VOFX34 BSP

Codice articolo: **811200050 / Nipple**



Valving style Poppet	**Body size** 3/4"
Sealing Nitrile NBR	**Interchange** Similar couplings (Oil&Gas)
Connection system Screw	**Disconnection system** Unscrew
Material Stainless steel (AISI 316L)	**Locking mechanism** Screw to connect
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure Pressure in one side	**Temperature** -20 / +100 °C; -4 / +212 °F
Applications Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Marine, Others, Earth moving, Oil & Gas	

Performance	METRIC
ISO DN (mm)	20
Max. Flow suggested (l/min)	212
Max. Operating pressure - coupled (Mpa)	20.7
Operating pressure - uncoupled (MPa)	20.7
Burst pressure - coupled (MPa)	82.8
Burst pressure - uncoupled (MPa)	62,1
Spillage (ml)	11.5
Manual connect torque (Nm)	2.3
Manual disconnect torque (Nm)	2.3

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	123,6
Length (mm)	83,2
Max. diameter (mm)	44,3
Weight (kg)	0,48

Related products

Product code	Type	Product name
811200050	Nipple	F/NIPPLE VOFX34 BSP

Spare kits

Product code	Product name
815700956	SPARE KIT OR NBR+BK F VOF34
815701146	SPARE KIT INTERNAL PARTS F-M VOFX34

Caps

Product code	Product name
815405012	ALUMINUM CAP N VOF34 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service