
F IRC34VZN BSP*

Codice articolo: **812100106** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Poppet	**Body size** 3/4"
Sealing FKM (VITON)	**Treatment** Zn-Ni
Interchange Similar couplings (Nordic)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety sleeve	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Earth moving, Agriculture, Vehicles

Performance	IMPERIAL
ISO DN (mm)	20
Max. Flow suggested (gpm)	56.18
Max. Operating pressure - coupled (psi)	4785
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	11600
Connect force (lbf)	38.25
Disconnect force (lbf)	10.125
Spillage (ml)	15

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	3,72
Length (in)	3
Max. diameter (in)	2,05
Weight (lb)	1,35

Related products

Product code	Type	Product name
812100107	Maschio	M IRC34VZN BSP

Spare kits

Product code	Product name
815700984	SPARE KIT OR VITON+BK F IRC34

Caps

Product code	Product name
815000048	PLASTIC CAP F IRC34 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service