
# M IRC38 NPTF

Codice articolo: **812102003** / **Male**







| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Zn-Ni |
| **Interchange**<br>Similar couplings (Nordic) | **Connection system**<br>Pull back the sleeve and push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball + Safety sleeve | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD NPTF (ANSI B.1.20.3) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Earth moving, Agriculture, Vehicles |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 10 |
| Max. Flow suggested (l/min) | 46 |
| Max. Operating pressure - coupled (Mpa) | 35 |
| Operating pressure - uncoupled (MPa) | 28 |
| Burst pressure - coupled (MPa) | 130 |
| Burst pressure - uncoupled (MPa) | 110 |
| Connect force (N) | 90 |
| Disconnect force (N) | 35 |
| Spillage (ml) | 2.5 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/8" |
| Overall length M+F (mm) | 76,4 |
| Length (mm) | 38 |
| Max. diameter (mm) | 19,9 |
| Weight (kg) | 0,06 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 812102002 | Femmina | F IRC38 NPTF |

## Caps

| Product code | Product name |
|---|---|
| 815000045 | PLASTIC CAP M IRC38 RED |
| 815009045 | PLASTIC CAP M IRC38 GREY* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service