F IR34VFA PL BSP*

Codice articolo: **820000032** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 3/4"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange Similar couplings (IR-V)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	IMPERIAL
Max. Flow suggested (gpm)	152.64
Max. Operating pressure - coupled (psi)	3625
Operating pressure - uncoupled (psi)	3625
Burst pressure - coupled (psi)	14500
Burst pressure - uncoupled (psi)	14500
Connect force (lbf)	39.375
Disconnect force (lbf)	10.125
Spillage (ml)	4.2

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,19
Length (in)	3,23
Max. diameter (in)	1,82
Weight (lb)	1,01

Related products

Product code	Type	Product name
820000033	Maschio	M IR34VFA PL BSP

Spare kits

Product code	Product name
815700734	SPARE KIT OR NBR+BK F IR34FA

Caps

Product code	Product name
815000006	PLASTIC PLUG F ISO-A/IR34 RED
815001016	PLASTIC PLUG F ISO-A 34 YELLOW**
815002016	PLASTIC PLUG F ISO-A 34 BLUE**
815003016	PLASTIC PLUG F ISO-A 34 BLACK**
815004016	PLASTIC PLUG F ISO-A 34 GREEN**
815005016	PLASTIC PLUG F ISO-A 34 WHITE**
815009016	PLASTIC PLUG F ISO-A 34 GREY**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service