F J12PL M22X1.5*

Codice articolo: **800712004** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Push
Disconnection system Pull	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD METRIC	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	12.5
Max. Flow suggested (l/min)	90
Max. Operating pressure - coupled (Mpa)	25
Operating pressure - uncoupled (MPa)	25
Burst pressure - coupled (MPa)	90
Burst pressure - uncoupled (MPa)	100
Connect force (N)	90
Disconnect force (N)	80
Spillage (ml)	1.8

Dimensions	METRIC
Port (A)	M22x1.5
Overall length M+F (mm)	107
Length (mm)	68,6
Max. diameter (mm)	38
Weight (kg)	0,23

Spare kits

Product code	Product name
815700928	SPARE KIT OR NBR+BK F IP12

Caps

Product code	Product name
815000004	PLASTIC PLUG F ISO-A/IR12 RED

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service