F A4QN 1/4 BSP EXT*

Codice articolo: **804800000** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Flat face	**Body size** 1/8"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread MALE THREAD BSPP (ISO 8434-6)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Material Handling, Robotics & Automation, Paper, Packaging, Leather, Utensili idraulici, Hydraulic Power Units, Injection Moulding, Die Casting, Others, Test Bench, Steel Mill, Rail, Road Construction, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Agricultural Attachments, Agricultural Machinery, Earth moving, Agriculture, Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	1.59
Max. Operating pressure - coupled (psi)	6090
Operating pressure - uncoupled (psi)	6090
Burst pressure - coupled (psi)	18270
Burst pressure - uncoupled (psi)	18270
Connect force (lbf)	27
Disconnect force (lbf)	5.625

Dimensions	IMPERIAL
Port (A)	1/4"
Overall length M+F (in)	3
Length (in)	1,72
Max. diameter (in)	0,79
Weight (lb)	0,14

Related products

Product code	Type	Product name
804800001	Maschio	M A4QN 1/4 BSP EXT

Caps

Product code	Product name
815100021	PLASTIC CAP M FF18 RED
815101021	PLASTIC CAP M FF18 YELLOW**
815102021	PLASTIC CAP M FF 18 BLUE**
815103021	PLASTIC CAP M FF 18 BLACK**
815104021	PLASTIC CAP M FF 18 GREEN**
815105021	PLASTIC CAP M FF 18 WHITE**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service