F A30 1-1/2 SAE (IN)

Codice articolo: **812504044** / **Female**

Valving style Flat face	**Body size** 1-1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Material Handling, Robots Automation, Paper, Packaging, Leather, Utensili idraulici, Hydraulic Power Units, Injection Molding, Die Casting, Others, Test Bench, Steel Mill, Rail, Road Construction, Foundation, Earth Moving, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Ceramic, Agricultural Attachments, Agricultural Machinery, Construction, Agriculture, Trucks & Vehicles, Oil & Gas

Performance	METRIC
ISO DN (mm)	38
Max. Flow suggested (l/min)	750
Max. Operating pressure - coupled (MPa)	27
Operating pressure - uncoupled (MPa)	27
Burst pressure - coupled (MPa)	81
Burst pressure - uncoupled (MPa)	81
Connect force (N)	390
Disconnect force (N)	70
Spillage (ml)	0.05

Dimensions	METRIC
Port (A)	1-7/8-12UN
Overall length M+F (mm)	214,9
Length (mm)	132,4
Max. diameter (mm)	80
Weight (kg)	3,16

Related products

Product code	Type	Product name
812504045	Maschio	M A30 1-1/2 SAE (IN)

Caps

Product code	Product name
815105014	ALUMINUM CAP F FF112 NATURAL
815100014	ALUMINUM CAP F FF112 RED*
815101014	ALUMINUM CAP F FF112 YELLOW*
815102014	ALUMINUM CAP F FF112 BLUE*
815103014	ALUMINUM CAP F FF112 BLACK*
815104014	ALUMINUM CAP F FF112 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service