F VT17ZN 1 FH CODE62

Codice articolo: **812424002** / **Female**

Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Zn-Ni
Interchange Stucchi profile VT	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect + Automatic lock sleeve	**Disconnectable under pressure** Yes
Thread FLANGE HEAD - WITH O-RING (ISO 6162-2 6000 psi & SAE J518)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Test Bench, Construction, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	7250
Operating pressure - uncoupled (psi)	5075
Burst pressure - coupled (psi)	18130
Burst pressure - uncoupled (psi)	15225
Spillage (ml)	0.02
Max. residual pressure during connection (in the male, female to drain) (psi)	3625
Max. residual pressure during connection (in the female, male to drain) (psi)	3625
Max. residual pressure during connection (in male and female) (psi)	2175
Max. residual pressure during disconnection (psi)	2175

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	12,93
Length (in)	6,12
Max. diameter (in)	2,03
Weight (lb)	2,93

Related products

Product code	Type	Product name
812424003	Maschio	M VT17ZN 1 FH CODE62

Caps

Product code	Product name
816103000	CAP FOR F VT17 POM BLACK
816105400	ALUMINIUM CAP F VT17 WHITE

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service