
# F IC9B 3/8 BSP

Codice articolo: **813500242** / **Female**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>3/8" |
| **Sealing**<br>EPDM | **Treatment**<br>Ossidazione dura |
| **Interchange**<br>Profilo Stucchi IC | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Alluminio |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-40 / +150 °C; -40 / +302 °F | **Applications**<br>Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors |

| Performance | IMPERIAL |
|---|---|
| Max. Operating pressure - coupled (psi) | 290 |
| Operating pressure - uncoupled (psi) | 290 |
| Burst pressure - coupled (psi) | 1160 |
| Burst pressure - uncoupled (psi) | 1160 |
| Connect force (lbf) | 20,7 |
| Disconnect force (lbf) | 5,4 |
| Spillage (ml) | 0.01 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 3/8" |
| Overall length M+F (in) | 3,37 |
| Length (in) | 2,34 |
| Max. diameter (in) | 1,22 |
| Weight (lb) | 0,13 |

Related products

| Product code | Type | Product name |
|---|---|---|
| 813517243 | Maschio | M IC9B 3/8 BSP EXT |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service