

# M IC13BD 1/2 BSP EXT*

Codice articolo: **813517253** / **Male**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>1/2" |
| **Sealing**<br>EPDM | **Treatment**<br>Ossidazione dura |
| **Interchange**<br>Profilo Stucchi IC | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Alluminio |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>MALE THREAD BSPP (ISO 8434-6) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-40 / +150 °C; -40 / +302 °F | **Applications**<br>Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors |

| Performance | METRIC |
|---|---|
| Max. Operating pressure - coupled (MPa) | 2 |
| Operating pressure - uncoupled (MPa) | 2 |
| Burst pressure - coupled (MPa) | 8 |
| Burst pressure - uncoupled (MPa) | 8 |
| Connect force (N) | 156 |
| Disconnect force (N) | 35 |
| Spillage (ml) | 0.01 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 1/2" |
| Overall length M+F (mm) | 112,8 |
| Length (mm) | 70,5 |
| Max. diameter (mm) | 29,5 |
| Weight (kg) | 0,05 |

Related products

| Product code | Type | Product name |
|---|---|---|
| 813500250 | Femmina | F IC13B 1/2 BSP |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service