F ICX9B 3/8 BSP

Codice articolo: **813600242** / **Female**

Valving style Flat face	**Body size** 09
Sealing EPDM	**Interchange** Profilo Stucchi IC
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors	

Performance	IMPERIAL
Max. Operating pressure - coupled (psi)	290
Operating pressure - uncoupled (psi)	290
Burst pressure - coupled (psi)	1160
Burst pressure - uncoupled (psi)	1160
Connect force (lbf)	20,7
Disconnect force (lbf)	5,4
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	3/8”
Overall length M+F (in)	3,37
Length (in)	2,34
Max. diameter (in)	1,22
Weight (lb)	0,4

Related products

Product code	Type	Product name
813617243	Maschio	M ICX9B 3/8 BSP EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service