M ICX7R 1/4 BSP EXT

Codice articolo: **813617201** / **Male**

Valving style Flat face	**Body size** 07
Sealing EPDM	**Interchange** Profilo Stucchi IC
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** MALE THREAD BSPP (ISO 8434-6)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors	

Performance	IMPERIAL
Max. Operating pressure - coupled (psi)	580
Operating pressure - uncoupled (psi)	580
Burst pressure - coupled (psi)	2320
Burst pressure - uncoupled (psi)	2320
Connect force (lbf)	92
Disconnect force (lbf)	4,3
Spillage (ml)	0

Dimensions	IMPERIAL
Port (A)	1/4”
Overall length M+F (in)	3,03
Length (in)	1,71
Max. diameter (in)	0,73
Weight (lb)	0,07

Related products

Product code	Type	Product name
813600200	Femmina	F ICX7R 1/4 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service