M ICX13R 1/2 BSP EXT

Codice articolo: **813617217** / **Male**

Valving style Flat face	**Body size** 13
Sealing EPDM	**Interchange** Profilo Stucchi IC
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** MALE THREAD BSPP (ISO 8434-6)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors	

Performance	METRIC
Max. Operating pressure - coupled (MPa)	2
Operating pressure - uncoupled (MPa)	2
Burst pressure - coupled (MPa)	8
Burst pressure - uncoupled (MPa)	8
Connect force (N)	156
Disconnect force (N)	35
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	1/2"
Overall length M+F (mm)	112,8
Length (mm)	81,1
Max. diameter (mm)	29,5
Weight (kg)	0,1

Related products

Product code	Type	Product name
813600216	Femmina	F ICX13R 1/2 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service