M ICX7B 1/4 BSP EXT

Codice articolo: **813617235** / **Male**

Valving style Flat face	**Body size** 07
Sealing EPDM	**Interchange** Profilo Stucchi IC
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** MALE THREAD BSPP (ISO 8434-6)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Data Center, Rail, Windmill, Medical devices, Others, Digital Transmitters, Electric Vehicles, HVAC/R, Laser, Defence, Semiconductors	

Performance	METRIC
Max. Operating pressure - coupled (MPa)	4
Operating pressure - uncoupled (MPa)	4
Burst pressure - coupled (MPa)	16
Burst pressure - uncoupled (MPa)	16
Connect force (N)	44
Disconnect force (N)	19
Spillage (ml)	0

Dimensions	METRIC
Port (A)	1/4"
Overall length M+F (mm)	77
Length (mm)	43,5
Max. diameter (mm)	18,5
Weight (kg)	0,03

Related products

Product code	Type	Product name
813600234	Femmina	F ICX7B 1/4 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service