M UQD02R 1/4 SAE EXT

Codice articolo: **813704201** / **Male**

Valving style Flat face	**Body size** 02
Sealing EPDM	**Interchange** OCP
Connection system Push	**Disconnection system** Pull back the sleeve
Material Acciaio inossidabile (AISI 303)	**Locking mechanism** Perno di ritenuta
Disconnectable under pressure No	**Thread** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Connectable under residual pressure No	**Temperature** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	IMPERIAL
Max. Operating pressure - coupled (psi)	160
Operating pressure - uncoupled (psi)	160
Burst pressure - coupled (psi)	580
Burst pressure - uncoupled (psi)	580
Connect force (lbf)	14
Spillage (ml)	0,01

Dimensions	IMPERIAL
Port (A)	7/16-20 UNF
Overall length M+F (in)	2,7
Length (in)	1,37
Max. diameter (in)	0,61
Weight (lb)	0,31

Related products

Product code	Type	Product name
813723200	Femmina	F UQD02R 1/4 HB

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service