# M UQD06B 1/2 SAE EXT

Codice articolo: **813704251** / **Male**

| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>06 |
| **Sealing**<br>EPDM | **Interchange**<br>OCP |
| **Connection system**<br>Push | **Disconnection system**<br>Pull back the sleeve |
| **Material**<br>Acciaio inossidabile (AISI 303) | **Locking mechanism**<br>Perno di ritenuta |
| **Disconnectable under pressure**<br>No | **Thread**<br>FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1) |
| **Connectable under residual pressure**<br>No | **Temperature**<br>-40 / +75 °C; -40 / +167 °F |
| **Applications**<br>Data Center | |

| Performance | METRIC |
|---|---|
| Max. Operating pressure - coupled (MPa) | 1,1 |
| Operating pressure - uncoupled (MPa) | 1,1 |
| Burst pressure - coupled (MPa) | 4 |
| Burst pressure - uncoupled (MPa) | 4 |
| Connect force (N) | 80 |
| Spillage (ml) | 0,02 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/4-16UNF |
| Length (mm) | 52,8 |
| Max. diameter (mm) | 25 |
| Weight (kg) | 0,06 |

Related products

| Product code | Type | Product name |
|---|---|---|
| 813723250 | Femmina | F UQD06B 1/2 HB |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service