F UQD04B 3/8 HB

Codice articolo: **813723242** / **Female**

Valving style Flat face	**Body size** 04
Sealing EPDM	**Interchange** OCP
Connection system Push	**Disconnection system** Pull back the sleeve
Material Acciaio inossidabile (AISI 303)	**Locking mechanism** Perno di ritenuta
Disconnectable under pressure No	**Thread** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connectable under residual pressure No	**Temperature** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	METRIC
Max. Operating pressure - coupled (MPa)	1,1
Operating pressure - uncoupled (MPa)	1,1
Burst pressure - coupled (MPa)	4
Burst pressure - uncoupled (MPa)	4
Connect force (N)	88
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	11.9
Overall length M+F (mm)	94,5
Length (mm)	76,2
Max. diameter (mm)	26
Weight (kg)	0,13

Related products

Product code	Type	Product name
813704243	Maschio	M UQD04B 3/8 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service