F UQD06B 1/2 HB

Codice articolo: **813723250** / **Female**

Valving style Flat face	**Body size** 06
Sealing EPDM	**Interchange** OCP
Connection system Push	**Disconnection system** Pull back the sleeve
Material Acciaio inossidabile (AISI 303)	**Locking mechanism** Perno di ritenuta
Disconnectable under pressure No	**Thread** HOSE BARB COMPATIBLE WITH PARKER PUSH-LOK®
Connectable under residual pressure No	**Temperature** -40 / +75 °C; -40 / +167 °F
Applications Data Center	

Performance	METRIC
Max. Operating pressure - coupled (MPa)	1,1
Operating pressure - uncoupled (MPa)	1,1
Burst pressure - coupled (MPa)	4
Burst pressure - uncoupled (MPa)	4
Connect force (N)	80
Spillage (ml)	0,02

Dimensions	METRIC
Port (A)	15.2
Length (mm)	83,3
Max. diameter (mm)	31
Weight (kg)	0,1

Related products

Product code	Type	Product name
813704251	Maschio	M UQD06B 1/2 SAE EXT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service