
F IR34V BSP

Codice articolo: **800100004** / **Female**



Valving style Poppet	**Body size** 3/4"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange Similar couplings (IR-V)	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
Max. Flow suggested (l/min)	148
Max. Operating pressure - coupled (MPa)	25
Operating pressure - uncoupled (MPa)	25
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	100
Connect force (N)	175
Disconnect force (N)	45
Spillage (ml)	4.2

Dimensions	METRIC
Port (A)	3/4"
Overall length M+F (mm)	86,3
Length (mm)	63,3
Max. diameter (mm)	38
Weight (kg)	0,68

Related products

Product code	Type	Product name
800100005	Maschio	M IR34V BSP

Spare kits

Product code	Product name
815700354	SPARE KIT OR NBR F IR34

Caps

Product code	Product name
815000006	PLASTIC PLUG F ISO-A/IR34 RED
815001016	PLASTIC PLUG F ISO-A 34 YELLOW*
815002016	PLASTIC PLUG F ISO-A 34 BLUE*
815003016	PLASTIC PLUG F ISO-A 34 BLACK*
815004016	PLASTIC PLUG F ISO-A 34 GREEN*
815005016	PLASTIC PLUG F ISO-A 34 WHITE*
815009016	PLASTIC PLUG F ISO-A 34 GREY*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service