
# M IR34V NPT

Codice articolo: **800101005** / **Male**




| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/4" |
| **Sealing**<br>FKM (VITON) | **Treatment**<br>Cr3 |
| **Interchange**<br>Similar couplings (IR-V) | **Connection system**<br>Pull back the sleeve and push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD NPT (ANSI B.1.20.1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-15 / +180 °C; +5 / +356 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Agriculture |

| Performance | METRIC |
|---|---|
| Max. Flow suggested (l/min) | 148 |
| Max. Operating pressure - coupled (MPa) | 25 |
| Operating pressure - uncoupled (MPa) | 25 |
| Burst pressure - coupled (MPa) | 100 |
| Burst pressure - uncoupled (MPa) | 100 |
| Connect force (N) | 175 |
| Disconnect force (N) | 45 |
| Spillage (ml) | 4.2 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/4" |
| Overall length M+F (mm) | 86,3 |
| Length (mm) | 44,5 |
| Max. diameter (mm) | 20,5 |
| Weight (kg) | 0,19 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 800101004 | Femmina | F IR34V NPT |

## Caps

| Product code | Product name |
|---|---|
| 815000007 | PLASTIC CAP M ISO-A/IR34 RED |
| 815001007 | PLASTIC CAP M IR34 YELLOW* |
| 815002007 | PLASTIC CAP M IR34 BLUE* |
| 815003007 | PLASTIC CAP M IR34 BLACK* |
| 815004007 | PLASTIC CAP M IR34 GREEN* |
| 815005007 | PLASTIC CAP M IR34 WHITE* |
| 815009017 | PLASTIC CAP M ISO-A 34 GREY* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service