F IV38HP BSP EXT DIN3852-2-B*

Codice articolo: **800200028** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Ball	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO14540 (High pressure)	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** No
Thread MALE THREAD METRIC DIN3852-1-A	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Rescue Equipments, Utensili idraulici

Performance	IMPERIAL
Max. Flow suggested (gpm)	6.095
Max. Operating pressure - coupled (psi)	10150

Dimensions	IMPERIAL
Port (A)	3/8"
Overall length M+F (in)	F+D-1,00
Length (in)	2,87
Max. diameter (in)	1,38
Weight (lb)	0,48

Spare kits

Product code	Product name
815700650	SPARE KIT OR NBR+BK F IV-HP38

Caps

Product code	Product name
815603012	PLASTIC CAP F IVHP38 BLACK
815605002	STEEL CAP F IVHP38 NATURAL

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service