F IFR8 M18X1.5 (WITHOUT PLUG)*

Codice articolo: **800212008** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style Flat face non spill	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 5676 "NF U 16-006"	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD METRIC	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Agriculture

Performance	METRIC
ISO DN (mm)	6.3
Max. Flow suggested (l/min)	46
Max. Operating pressure - coupled (MPa)	15
Operating pressure - uncoupled (MPa)	15
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	30
Connect force (N)	170
Disconnect force (N)	27
Spillage (ml)	0.06

Dimensions	METRIC
Port (A)	M18x1.5
Overall length M+F (mm)	F+D-15
Length (mm)	54,2
Max. diameter (mm)	44
Weight (kg)	0,34

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service