# M BIRV200 BSP*

Codice articolo: **800500115** / **Male** / ***Prodotto disponibile su richiesta**

| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>2" |
| **Sealing**<br>FKM (VITON) | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 7241 A | **Connection system**<br>Pull back the sleeve and push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD BSPP (ISO 1179-1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-15 / +180 °C; +5 / +356 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Foundation, Material Handling, Road Construction, Construction, Agriculture |

| Performance | IMPERIAL |
|---|---|
| ISO DN (mm) | 51 |
| Max. Flow suggested (gpm) | 265 |
| Max. Operating pressure - coupled (psi) | 1885 |
| Operating pressure - uncoupled (psi) | 1885 |
| Burst pressure - coupled (psi) | 5800 |
| Burst pressure - uncoupled (psi) | 5800 |
| Connect force (lbf) | 60.75 |
| Disconnect force (lbf) | 13.5 |
| Spillage (ml) | 75 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 2" |
| Overall length M+F (in) | 7,92 |
| Length (in) | 3,94 |
| Max. diameter (in) | 3,25 |
| Weight (lb) | 3,17 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 800500114 | Femmina | F BIRV200 BSP |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service