# F BIRV38 NPT*

Codice articolo: **800501102** / **Female** / ***Prodotto disponibile su richiesta**

| | |
|---|---|
| **Valving style**<br>Poppet | **Body size**<br>3/8" |
| **Sealing**<br>FKM (VITON) | **Treatment**<br>Cr3 |
| **Interchange**<br>ISO 7241 A | **Connection system**<br>Pull back the sleeve and push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD NPT (ANSI B.1.20.1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-15 / +180 °C; +5 / +356 °F | **Applications**<br>Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Foundation, Material Handling, Road Construction, Construction, Agriculture |

| Performance | METRIC |
|---|---|
| ISO DN (mm) | 10 |
| Max. Flow suggested (l/min) | 46 |
| Max. Operating pressure - coupled (MPa) | 30 |
| Operating pressure - uncoupled (MPa) | 30 |
| Burst pressure - coupled (MPa) | 100 |
| Burst pressure - uncoupled (MPa) | 100 |
| Connect force (N) | 90 |
| Disconnect force (N) | 30 |
| Spillage (ml) | 1.2 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 3/8" |
| Overall length M+F (mm) | 76,8 |
| Length (mm) | 56,1 |
| Max. diameter (mm) | 31 |
| Weight (kg) | 0,15 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 800501103 | Maschio | M BIRV38 NPT |

## Spare kits

| Product code | Product name |
|---|---|
| 815700188 | SPARE KIT OR VITON+BK F BIR38** |

## Caps

| Product code | Product name |
|---|---|
| 815000014 | PLASTIC PLUG F ISO-A 38 RED |

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service