F BIR100 BSPT*

Codice articolo: **800503008** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Foundation, Material Handling, Road Construction, Construction, Agriculture

Performance	IMPERIAL
ISO DN (mm)	25
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	3335
Operating pressure - uncoupled (psi)	3335
Burst pressure - coupled (psi)	11600
Burst pressure - uncoupled (psi)	11600
Connect force (lbf)	42.75
Disconnect force (lbf)	12.375
Spillage (ml)	9

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	5,01
Length (in)	3,82
Max. diameter (in)	2,13
Weight (lb)	1,7

Related products

Product code	Type	Product name
800503009	Maschio	M BIR100 BSPT

Spare kits

Product code	Product name
815700178	SPARE KIT OR NBR+BK F BIR100

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service