M BIR112 BSPT*

Codice articolo: **800503013** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 1-1/2"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 7241 A	**Connection system** Pull back the sleeve and push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Foundation, Material Handling, Road Construction, Construction, Agriculture

Performance	IMPERIAL
ISO DN (mm)	38
Max. Flow suggested (gpm)	198.75
Max. Operating pressure - coupled (psi)	2610
Operating pressure - uncoupled (psi)	2610
Burst pressure - coupled (psi)	9280
Burst pressure - uncoupled (psi)	9280
Connect force (lbf)	56.25
Disconnect force (lbf)	15.75
Spillage (ml)	49

Dimensions	IMPERIAL
Port (A)	1-1/2"
Overall length M+F (in)	5,76
Length (in)	3,35
Max. diameter (in)	2,62
Weight (lb)	1,94

Related products

Product code	Type	Product name
800503012	Femmina	F BIR112 BSPT

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service