







Body size 1/4"	Valving style Poppet
Interchange ISO 7241 B	Sealing FKM (VITON)
Connection system Pull back the sleeve and push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Cr3
Locking mechanism Locking ball	Disconnectable under pressure No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	Connectable under residual pressure No
Temperature -15 / +180 °C; +5 / +356 °F	Applications Oil & Gas, Industry, Chemical & Food Industry

Performance	METRIC
ISO DN (mm)	6.3
Flow (I/min)	Da 20 a 50
Max. Flow suggested (I/min)	24
Max. Operating pressure - coupled (Mpa)	35
Operating pressure - uncoupled (mpa)	35
Burst pressure - coupled (mpa)	100
Burst pressure - uncoupled (mpa)	100
Connect force (N)	50
Disconnect force (N)	35
Spillage (ml)	0.33

Dimensions	METRIC
Port (A)	9/16-18UNF
Overall length M+F (mm)	78,7
Length (mm)	61
Max. diameter (mm)	27
Weight (kg)	0,13

Related products

Product code	Туре	Product name
800604101	Maschio	M IRB14V 3/8 SAE

Spare kits

Product code	Product name
815700216	SPARE KIT OR VITON+BK F ISOB 14

Caps

Product code	Product name	
815000032	PLASTIC PLUG F ISO-B 14 RED	
815003032	PLASTIC PLUG F ISO-B 14 BLACK**	

^{**}Product available upon request