F FIRG45V 2 BSP*

Codice articolo: **800800118** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 2"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Test Bench, Utensili idraulici, Construction, Agriculture, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	265
Max. Operating pressure - coupled (psi)	3625
Operating pressure - uncoupled (psi)	1160
Burst pressure - coupled (psi)	11600
Burst pressure - uncoupled (psi)	4640
Connect force (lbf)	105.75
Disconnect force (lbf)	22.5
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	2"
Overall length M+F (in)	9,51
Length (in)	6,17
Max. diameter (in)	3,94
Weight (lb)	11,25

Related products

Product code	Type	Product name
800800119	Maschio	M FIRG45V 2 BSP

Caps

Product code	Product name
815105016	ALUMINUM CAP F FF200 NATURAL
815100016	ALUMINUM CAP F FF200 RED**
815101016	ALUMINUM CAP F FF200 YELLOW**
815102016	ALUMINUM CAP F FF200 BLUE**
815103016	ALUMINUM CAP F FF200 BLACK**
815104016	ALUMINUM CAP F FF200 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service