
M FIRG45V 2 SAE*

Codice articolo: **800804119** / **Male** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 2"
Sealing FKM (VITON)	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety lock	**Disconnectable under pressure** No
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** No
Temperature -15 / +180 °C; +5 / +356 °F	**Applications** Agricultural Machinery, Agricultural Attachments, Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Test Bench, Utensili idraulici, Construction, Agriculture, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	265
Max. Operating pressure - coupled (psi)	2900
Operating pressure - uncoupled (psi)	2320
Burst pressure - coupled (psi)	11600
Burst pressure - uncoupled (psi)	9280
Connect force (lbf)	105.75
Disconnect force (lbf)	22.5
Spillage (ml)	0.01

Dimensions	IMPERIAL
Port (A)	2-1/2-12UN
Overall length M+F (in)	9,51
Length (in)	4,87
Max. diameter (in)	2,87

Related products

Product code	Type	Product name
800804118	Femmina	F FIRG45V 2 SAE

Spare kits

Product code	Product name
815700798	SPARE KIT OR VITON+BK M FF 200**

Caps

Product code	Product name
815105019	ALUMINUM CAP M FF200 NATURAL
815100019	ALUMINUM CAP M FF200 RED**
815101019	ALUMINUM CAP M FF200 YELLOW**
815102019	ALUMINUM CAP M FF200 BLUE**
815103019	ALUMINUM CAP M FF200 BLACK**
815104019	ALUMINUM CAP M FF200 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service