

F FIRG17QK 1 BSP

Codice articolo: 800900702 / Female



Body size 3/4"	Valving style Flat face
Interchange ISO 16028	Sealing KALREZ
Connection system Push	Disconnection system Pull back the sleeve
Material Carbon steel + Stainless steel (AISI 303)	Treatment Stainless steel + QPQ
Locking mechanism Locking ball + Safety lock	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure No
Temperature -25 / +300 °C; -13 / +572 °F	Applications Oil & Gas, Industry, Cooling, Chemical & Food Industry

Performance	IMPERIAL	Dimensions	IMPERIAL
ISO DN (mm)	19	Port (A)	1"
Flow (gpm)	From 39,75 to 92,75	Overall length M+F (in)	6,04
Max. Flow suggested (gpm)	5.3	Length (in)	3,67
Max. Operating pressure - coupled (psi)	725	Max. diameter (in)	1,89
Operating pressure - uncoupled (psi)	725	Weight (lb)	1,69
Burst pressure - coupled (psi)	14500		
Burst pressure - uncoupled (psi)	8700		
Connect force (lbf)	49.5		
Disconnect force (lbf)	15.75		
Spillage (ml)	0.03		

Related products

Product code	Type	Product name
800900703	Maschio	M FIRG17QK 1 BSP

Caps

Product code	Product name
815100010	PLASTIC CAP F FF34 RED
815200008	PLASTIC FLIP CAP F FF34 RED
816005010	ALUMINUM CAP F FF34 NATURAL
815103010	PLASTIC CAP F FF34 BLACK *
815102010	PLASTIC CAP F FF34 BLUE *
815104010	PLASTIC CAP F FF34 GREEN *
815110006	PLASTIC CAP F FF34 MAGENTA *
815107006	PLASTIC CAP F FF34 ORANGE *
815105010	PLASTIC CAP F FF34 WHITE *
815101010	PLASTIC CAP F FF34 YELLOW *
815203008	PLASTIC FLIP CAP F FF34 BLACK *
815202008	PLASTIC FLIP CAP F FF34 BLUE *
815204008	PLASTIC FLIP CAP F FF34 GREEN *
815201008	PLASTIC FLIP CAP F FF34 YELLOW *

*Product available upon request