

Body size 3/8"	Valving style Flat face
Interchange	Sealing
ISO 16028	Nitrile NBR
Connection system Push	Disconnection system Pull back the sleeve
Material	Treatment
Carbon steel	Cr3
Locking mechanism	Disconnectable under pressure
Locking ball + Safety lock	No
Thread	Connectable under residual pressure
MALE THREAD JIC - (ISO 8434-2 & SAE J514)	No
<b>Temperature</b> -20 / +100 °C; -4 / +212 °F	Applications Earth moving, Agriculture, Vehicles, Oil & Gas, Industry, Hydraulic Tools

Performance	METRIC
ISO DN (mm)	10
Flow (I/min)	Da 20 a 50
Max. Flow suggested (I/min)	46
Max. Operating pressure - coupled (Mpa)	35
Operating pressure - uncoupled (mpa)	35
Burst pressure - coupled (mpa)	100
Burst pressure - uncoupled (mpa)	100
Connect force (N)	170
Disconnect force (N)	40
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	9/16-18UNF
Overall length M+F (mm)	127,1
Length (mm)	69
Max. diameter (mm)	29
Weight (kg)	0,15

## Related products

Product code	Туре	Product name
801306002	Femmina	F A9 3/8 JIC

## Spare kits

Product code	Product name
815700337	SPARE KIT OR NBR+BK M FF 38

## Caps

Product code	Product name
815100025	PLASTIC CAP M FF38 RED
816005005	ALUMINUM CAP M FF38 NATURAL
815103025	PLASTIC CAP M FF38 BLACK*
815102025	PLASTIC CAP M FF38 BLUE*
815104025	PLASTIC CAP M FF38 GREEN*
815110027	PLASTIC CAP M FF38 MAGENTA BIG RING*
815107027	PLASTIC CAP M FF38 ORANGE BIG RING *
815105025	PLASTIC CAP M FF38 WHITE*
815101025	PLASTIC CAP M FF38 YELLOW*

<sup>\*</sup>Product available upon request