M A9HP 1/2 BSP*

Codice articolo: **801600009** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 3/8"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange Stucchi profile A-HP	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball + Safety sleeve	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** No
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Rescue Equipments, Hydraulic Power Units, Utensili idraulici

Performance	IMPERIAL
Max. Flow suggested (gpm)	12.19
Max. Operating pressure - coupled (psi)	10150
Operating pressure - uncoupled (psi)	10150
Burst pressure - coupled (psi)	26100
Burst pressure - uncoupled (psi)	29000
Connect force (lbf)	46.125
Disconnect force (lbf)	11.25
Spillage (ml)	0.02

Dimensions	IMPERIAL
Port (A)	1/2"
Overall length M+F (in)	4,58
Length (in)	2,46
Max. diameter (in)	1,14
Weight (lb)	0,34

Related products

Product code	Type	Product name
801600008	Femmina	F A9HP 1/2 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service