
# F A4HP 1/8 NPT

Codice articolo: **801601014** / **Female**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>1/8" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 |
| **Interchange**<br>Stucchi profile A-HP | **Connection system**<br>Push |
| **Disconnection system**<br>Pull back the sleeve | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Locking ball + Safety sleeve | **Disconnectable under pressure**<br>No |
| **Thread**<br>FEMALE THREAD NPT (ANSI B.1.20.1) | **Connectable under residual pressure**<br>No |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Rescue Equipments, Hydraulic Power Units, Utensili idraulici |

| Performance | METRIC |
|---|---|
| Max. Flow suggested (l/min) | 6 |
| Max. Operating pressure - coupled (MPa) | 70 |
| Operating pressure - uncoupled (MPa) | 70 |
| Burst pressure - coupled (MPa) | 160 |
| Burst pressure - uncoupled (MPa) | 160 |
| Connect force (N) | 95 |
| Disconnect force (N) | 40 |
| Spillage (ml) | 0.04 |

| Dimensions | METRIC |
|---|---|
| Port (A) | 1/8" |
| Overall length M+F (mm) | 72,3 |
| Length (mm) | 44 |
| Max. diameter (mm) | 22 |
| Weight (kg) | 0,09 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 801601015 | Maschio | M A4HP 1/8 NPT |

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service