M FL21 1-1/4 BSP

Codice articolo: **802400115** / **Male**

Valving style Flat face	**Body size** 1"
Sealing FKM (VITON)	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Medical devices, Semiconductors, Packaging, Food Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
ISO DN (mm)	31.5
Max. Flow suggested (l/min)	378
Max. Operating pressure - coupled (MPa)	28
Operating pressure - uncoupled (MPa)	28
Burst pressure - coupled (MPa)	90
Burst pressure - uncoupled (MPa)	80
Connect force (N)	280
Disconnect force (N)	90
Spillage (ml)	0.04

Dimensions	METRIC
Port (A)	1-1/4"
Overall length M+F (mm)	173
Length (mm)	90
Max. diameter (mm)	36
Weight (kg)	0,67

Related products

Product code	Type	Product name
802400114	Femmina	F FL21 1-1/4 BSP

Spare kits

Product code	Product name
815700255	SPARE KIT OR VITON+BK M FF 100

Caps

Product code	Product name
815100015	PLASTIC CAP M FF100 RED
816005013	ALUMINUM CAP M FF100 NATURAL
815101015	PLASTIC CAP M FF100 YELLOW*
815102015	PLASTIC CAP M FF100 BLUE*
815103015	PLASTIC CAP M FF100 BLACK*
815104015	PLASTIC CAP M FF100 GREEN*
815105015	PLASTIC CAP M FF100 WHITE*
815107013	PLASTIC CAP M FF100 ORANGE*
815110013	PLASTIC CAP M FF100 MAGENTA*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service