
F FL45E 2? BSP*

Codice articolo: **802400216** / **Female** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 2"
Sealing EPDM	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Medical devices, Semiconductors, Packaging, Food Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	IMPERIAL
Max. Flow suggested (gpm)	265
Max. Operating pressure - coupled (psi)	2175
Operating pressure - uncoupled (psi)	1015
Burst pressure - coupled (psi)	8700
Burst pressure - uncoupled (psi)	4060
Connect force (lbf)	110.25
Disconnect force (lbf)	15.75
Spillage (ml)	0.1

Dimensions	IMPERIAL
Port (A)	2"
Overall length M+F (in)	9,51
Length (in)	6,17
Max. diameter (in)	3,94
Weight (lb)	11,53

Related products

Product code	Type	Product name
802400217	Maschio	M FL45E 2? BSP

Caps

Product code	Product name
815105016	ALUMINUM CAP F FF200 NATURAL
815100016	ALUMINUM CAP F FF200 RED**
815101016	ALUMINUM CAP F FF200 YELLOW**
815102016	ALUMINUM CAP F FF200 BLUE**
815103016	ALUMINUM CAP F FF200 BLACK**
815104016	ALUMINUM CAP F FF200 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service