M FL4E 1/8 BSP*

Codice articolo: **802400223** / **Male** / ***Prodotto disponibile su richiesta**

Valving style Flat face	**Body size** 1/8"
Sealing EPDM	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Medical devices, Semiconductors, Packaging, Food Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
Max. Flow suggested (l/min)	6
Max. Operating pressure - coupled (MPa)	35
Operating pressure - uncoupled (MPa)	35
Burst pressure - coupled (MPa)	140
Burst pressure - uncoupled (MPa)	140
Connect force (N)	140
Disconnect force (N)	30
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	1/8"
Overall length M+F (mm)	68,4
Length (mm)	36,3
Max. diameter (mm)	11,6
Weight (kg)	0,04

Related products

Product code	Type	Product name
802400222	Femmina	F FL4E 1/8 BSP

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service