F FL7 3/8 SAE*

Codice articolo: **802404102** / **Female** / ***Prodotto disponibile su richiesta**

Stucchi®

Valving style
Flat face

Body size
1/4"

Sealing
FKM (VITON)

Interchange
ISO 16028

Connection system
Push

Disconnection system
Pull back the sleeve

Material
Stainless steel (AISI 316L)

Locking mechanism
Locking ball + Safety lock

Disconnectable under pressure
No

Thread
FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)

Connectable under residual pressure
No

Temperature
-15 / +180 °C; +5 / +356 °F

Applications
Medical devices, Semiconductors, Packaging, Food Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	24
Max. Operating pressure - coupled (MPa)	35
Operating pressure - uncoupled (MPa)	33
Burst pressure - coupled (MPa)	140
Burst pressure - uncoupled (MPa)	120
Connect force (N)	140
Disconnect force (N)	30
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	9/16-18UNF
Overall length M+F (mm)	96,1
Length (mm)	53,2
Max. diameter (mm)	28
Weight (kg)	0,15

Related products

Product code	Type	Product name
802404103	Maschio	M FL7 3/8 SAE

Caps

Product code	Product name
815100000	PLASTIC CAP F FF14 RED
816005002	ALUMINUM CAP F FF14 NATURAL
815101000	PLASTIC CAP F FF14 YELLOW**
815102000	PLASTIC CAP F FF14 BLUE**
815103000	PLASTIC CAP F FF14 BLACK**
815104000	PLASTIC CAP F FF14 GREEN**
815105000	PLASTIC CAP F FF14 WHITE**
815107000	PLASTIC CAP F FF14 ORANGE**
815110000	PLASTIC CAP F FF14 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service