
M FL45 2? SAE*

Codice articolo: **802404123** / **Male** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 2"
Sealing FKM (VITON)	**Interchange** ISO 16028
Connection system Push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L)	**Locking mechanism** Locking ball + Safety lock
Disconnectable under pressure No	**Thread** FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Medical devices, Semiconductors, Packaging, Food Beverage, Laser, HVAC/R, Electric Vehicles, Digital Transmitters, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Windmill, Test Bench, Steel Mill, Rail, Data Center, Coil Tubing Unit, Drilling Rig, Oil & Gas	

Performance	METRIC
Max. Flow suggested (l/min)	1000
Max. Operating pressure - coupled (MPa)	15
Operating pressure - uncoupled (MPa)	15
Burst pressure - coupled (MPa)	60
Burst pressure - uncoupled (MPa)	60
Connect force (N)	490
Disconnect force (N)	70
Spillage (ml)	0.1

Dimensions	METRIC
Port (A)	2-1/2-12UN
Overall length M+F (mm)	241,5
Length (mm)	123,8
Max. diameter (mm)	83,5
Weight (kg)	2,34

Related products

Product code	Type	Product name
802404122	Femmina	F FL45 2? SAE

Spare kits

Product code	Product name
815700798	SPARE KIT OR VITON+BK M FF 200**

Caps

Product code	Product name
815105019	ALUMINUM CAP M FF200 NATURAL
815100019	ALUMINUM CAP M FF200 RED**
815101019	ALUMINUM CAP M FF200 YELLOW**
815102019	ALUMINUM CAP M FF200 BLUE**
815103019	ALUMINUM CAP M FF200 BLACK**
815104019	ALUMINUM CAP M FF200 GREEN**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service