## <u>F A7SS L10<sup>\*</sup></u> Codice articolo: 803008008 / Female / \*Prodotto disponibile su richiesta



Body size	Valving style
1/4*	Flat face
Interchange	Sealing
ISO 16028	Nitrile NBR
Connection system	Disconnection system
Push	Pull back the sleeve
Material	Treatment
Carbon steel	Cr3
Locking mechanism	Disconnectable under pressure
Locking ball + Safety lock	No
Thread	Connectable under residual pressure
MALE THREAD METRIC L - 24° CONE (ISO 8434-1 & DIN 2353)	No
Temperature	Applications
-20 / +100 °C; -4 / +212 °F	Earth moving, Agriculture, Vehicles, Oil & Gas, Industry, Hydraulic Tools

Performance	METRIC
ISO DN (mm)	6.3
Flow (I/min)	Da 20 a 50
Max. Flow suggested (I/min)	24
Max. Operating pressure - coupled (Mpa)	42
Operating pressure - uncoupled (mpa)	42
Burst pressure - coupled (mpa)	126
Burst pressure - uncoupled (mpa)	126
Connect force (N)	150
Disconnect force (N)	45
Spillage (ml)	0.01

Dimensions	METRIC
Port (A)	M16x1.5
Overall length M+F (mm)	95,2
Length (mm)	53,1
Max. diameter (mm)	28
Weight (kg)	0,15

## Caps

Product name
PLASTIC CAP F FF14 RED
ALUMINUM CAP F FF14 NATURAL
PLASTIC CAP F FF14 BLACK**
PLASTIC CAP F FF14 BLUE**
PLASTIC CAP F FF14 GREEN **
PLASTIC CAP F FF14 MAGENTA**
PLASTIC CAP F FF14 ORANGE**
PLASTIC CAP F FF14 WHITE **
PLASTIC CAP F FF14 YELLOW**

\*\*Product available upon request

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved. Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service