F IRBO34E NPT*

Codice articolo: **804501208** / **Female** / ***Prodotto disponibile su richiesta**

Valving style Poppet	**Body size** 3/4"
Sealing EPDM	**Interchange** ISO 7241 B
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Brass	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD NPT (ANSI B.1.20.1)
Connectable under residual pressure No	**Temperature** -40 / +150 °C; -40 / +302 °F
Applications Drilling Rig, Coil Tubing Unit, Steel Mill, Test Bench, Chemical Pharma, Others, Die Casting, Injection Molding, Electric Vehicles, Hydraulic Power Units, Food Beverage, Semiconductors, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	19
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	1812.5
Operating pressure - uncoupled (psi)	18125
Burst pressure - coupled (psi)	8700
Burst pressure - uncoupled (psi)	8700
Connect force (lbf)	28.125
Disconnect force (lbf)	9
Spillage (ml)	9.4

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,37
Length (in)	3,55
Max. diameter (in)	1,97
Weight (lb)	1,36

Related products

Product code	Type	Product name
804501209	Maschio	M IRBO34E NPT

Spare kits

Product code	Product name
815700234	SPARE KIT OR EPDM+BK F ISOB 34 **

Caps

Product code	Product name
815000038	PLASTIC PLUG F ISO-B 34 RED
815003038	PLASTIC PLUG F ISO-B 34 BLACK **

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service