
F IRBX34PL BSP*

Codice articolo: **804600122** / **Female** / ***Prodotto disponibile su richiesta**





Valving style Poppet	**Body size** 3/4"
Sealing FKM (VITON)	**Interchange** ISO 7241 B
Connection system Pull back the sleeve and push	**Disconnection system** Pull back the sleeve
Material Stainless steel (AISI 316L) + Retainer in Brass	**Locking mechanism** Locking ball
Disconnectable under pressure No	**Thread** FEMALE THREAD BSPP (ISO 1179-1)
Connectable under residual pressure No	**Temperature** -15 / +180 °C; +5 / +356 °F
Applications Rail, Semiconductors, Food Beverage, Defence, Hydraulic Power Units, Electric Vehicles, Injection Molding, Die Casting, Others, Marine, Chemical Pharma, Test Bench, Steel Mill, Road Construction, Material Handling, Foundation, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Agricultural Attachments, Agricultural Machinery, Construction, Agriculture, Oil & Gas	

Performance	IMPERIAL
ISO DN (mm)	19
Max. Flow suggested (gpm)	39.22
Max. Operating pressure - coupled (psi)	2320
Operating pressure - uncoupled (psi)	2320
Burst pressure - coupled (psi)	11600
Burst pressure - uncoupled (psi)	11600
Connect force (lbf)	30.375
Disconnect force (lbf)	12.375
Spillage (ml)	9.4

Dimensions	IMPERIAL
Port (A)	3/4"
Overall length M+F (in)	4,37
Length (in)	3,55
Max. diameter (in)	1,97
Weight (lb)	1,18

Related products

Product code	Type	Product name
804600123	Maschio	M IRBX34PL BSP

Spare kits

Product code	Product name
815700222	SPARE KIT OR VITON+BK F ISOB 34

Caps

Product code	Product name
815000038	PLASTIC PLUG F ISO-B 34 RED
815003038	PLASTIC PLUG F ISO-B 34 BLACK**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service