
M APM17 BR6.5/66.5 1 BSP*

Codice articolo: **805100015** / **Male** / ***Prodotto disponibile su richiesta**



Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3
Interchange ISO 16028	**Connection system** Push
Disconnection system Pull back the sleeve	**Material** Carbon steel
Locking mechanism Locking ball	**Disconnectable under pressure** No
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in male side only
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Earth Moving, Leather, Utensili idraulici, Hydraulic Power Units, Others, Test Bench, Rail, Road Construction, Material Handling, Foundation, Coil Tubing Unit, Drilling Rig, Demolition, Construction Equipment Attachments, Agricultural Attachments, Agricultural Machinery, Construction, Agriculture, Trucks & Vehicles, Oil & Gas

Performance	METRIC
ISO DN (mm)	19
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (MPa)	33
Operating pressure - uncoupled (MPa)	33
Burst pressure - coupled (MPa)	100
Burst pressure - uncoupled (MPa)	120
Connect force (N)	260
Disconnect force (N)	80
Spillage (ml)	0.18

Dimensions	METRIC
Port (A)	1"
Length (mm)	108,5
Max. diameter (mm)	49,8
Weight (kg)	0,75

Spare kits

Product code	Product name
815700343	SPARE KIT OR NBR+BK M FF 34

Caps

Product code	Product name
815100013	PLASTIC CAP M FF34 RED
816005011	ALUMINUM CAP M FF34 NATURAL
815101013	PLASTIC CAP M FF34 YELLOW**
815102013	PLASTIC CAP M FF34 BLUE**
815103013	PLASTIC CAP M FF34 BLACK**
815104013	PLASTIC CAP M FF34 GREEN**
815105013	PLASTIC CAP M FF34 WHITE**
815107031	PLASTIC CAP M FF34 ORANGE**
815110031	PLASTIC CAP M FF34 MAGENTA**

***Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service