


F FIRG9 BT30 1/2 BSP*

Codice articolo: 805300008 / Female / *Prodotto disponibile su richiesta



Body size 3/8"	Valving style Flat face
Interchange ISO 16028	Sealing Nitrile NBR
Connection system Push	Disconnection system Pull back the sleeve
Material Carbon steel	Treatment Cr3
Locking mechanism Locking ball + Safety lock	Disconnectable under pressure No
Thread FEMALE THREAD BSPP (ISO 1179-1)	Connectable under residual pressure No
Temperature -20 / +100 °C; -4 / +212 °F	Applications Earth moving, Agriculture, Vehicles, Oil & Gas, Industry, Hydraulic Tools, Chemical & Food Industry

Performance	IMPERIAL	Dimensions	IMPERIAL
ISO DN (mm)	10	Port (A)	1/2"
Flow (gpm)	From 5,3 to 13,25	Overall length M+F (in)	4,58
Max. Flow suggested (gpm)	12.19	Length (in)	2,72
Max. Operating pressure - coupled (psi)	4350	Max. diameter (in)	1,14
Operating pressure - uncoupled (psi)	1740	Weight (lb)	0,57
Burst pressure - coupled (psi)	17400		
Burst pressure - uncoupled (psi)	6960		
Connect force (lbf)	33.75		
Disconnect force (lbf)	9		
Spillage (ml)	0.01		

Caps

Product code	Product name
815100002	PLASTIC CAP F FF38 RED
815200002	PLASTIC FLIP CAP F FF38 RED
816005004	ALUMINUM CAP F FF38 NATURAL
815103002	PLASTIC CAP F FF38 BLACK **
815102002	PLASTIC CAP F FF38 BLUE **
815104002	PLASTIC CAP F FF38 GREEN **
815110002	PLASTIC CAP F FF38 MAGENTA **
815107002	PLASTIC CAP F FF38 ORANGE **
815105002	PLASTIC CAP F FF38 WHITE **
815101002	PLASTIC CAP F FF38 YELLOW **
815203002	PLASTIC FLIP CAP F FF38 BLACK **
815202002	PLASTIC FLIP CAP F FF38 BLUE **
815204002	PLASTIC FLIP CAP F FF38 GREEN **
815201002	PLASTIC FLIP CAP F FF38 YELLOW **

**Product available upon request