
F VEP30P 1-1/2 BSP

Codice articolo: **807200016** / **Female**



Valving style Flat face	**Body size** 1-1/2"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VEP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** Yes
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Steel Mill, Die Casting, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	750
Max. Operating pressure - coupled (MPa)	40
Operating pressure - uncoupled (MPa)	27
Burst pressure - coupled (MPa)	110
Burst pressure - uncoupled (MPa)	80
Spillage (ml)	0.2
Manual connect torque (Nm)	26
Manual disconnect torque (Nm)	12.5
Tightening torque (Nm)	155-175

Dimensions	METRIC
Port (A)	1-1/2"
Overall length M+F (mm)	253,9
Length (mm)	133,5
Max. diameter (mm)	92
Weight (kg)	3,81

Related products

Product code	Type	Product name
807200017	Maschio	M VEP30P 1-1/2 BSP

Caps

Product code	Product name
815303136	PLASTIC CAP F VEP30 BLACK
815305082	ALUMINUM CAP F VEP30 NATURAL
815300082	ALUMINUM PLUG F VEP30 RED *
815301082	ALUMINUM PLUG F VEP30 YELLOW *
815302082	ALUMINUM PLUG F VEP30 BLUE *
815303082	ALUMINUM PLUG F VEP30 BLACK *
815304082	ALUMINUM PLUG F VEP30 GREEN *

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service