M VEP30P 1-1/2 NPT

Codice articolo: **807201017** / **Male**

Valving style Flat face	**Body size** 1-1/2"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VEP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** Yes
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Steel Mill, Die Casting, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	750
Max. Operating pressure - coupled (MPa)	40
Operating pressure - uncoupled (MPa)	40
Burst pressure - coupled (MPa)	110
Burst pressure - uncoupled (MPa)	110
Spillage (ml)	0.2
Manual connect torque (Nm)	26
Manual disconnect torque (Nm)	12.5
Tightening torque (Nm)	155-175

Dimensions	METRIC
Port (A)	1-1/2"
Overall length M+F (mm)	253,9
Length (mm)	150
Max. diameter (mm)	89,8
Weight (kg)	3,18

Related products

Product code	Type	Product name
807201016	Femmina	F VEP30P 1-1/2 NPT

Spare kits

Product code	Product name
815700741	SPARE KIT OR NBR+OR HOLDER M VEP30

Caps

Product code	Product name
815303137	PLASTIC CAP M VEP30 BLACK
815305083	ALUMINUM CAP M VEP30 NATURAL
815300083	ALUMINUM CAP M VEP30 RED*
815301083	ALUMINUM CAP M VEP30 YELLOW*
815302083	ALUMINUM CAP M VEP30 BLUE*
815303083	ALUMINUM CAP M VEP30 BLACK*
815304083	ALUMINUM CAP M VEP30 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service