
M VEP17P 1 SAE

Codice articolo: **807204013** / **Male**



Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VEP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** Yes
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Steel Mill, Die Casting, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (MPa)	50
Operating pressure - uncoupled (MPa)	50
Burst pressure - coupled (MPa)	125
Burst pressure - uncoupled (MPa)	125
Spillage (ml)	0.01
Manual connect torque (Nm)	5.6
Manual disconnect torque (Nm)	3.6
Tightening torque (Nm)	90-110

Dimensions	METRIC
Port (A)	1-5/16-12UN
Overall length M+F (mm)	190,5
Length (mm)	113,6
Max. diameter (mm)	54,8
Weight (kg)	1,01

Related products

Product code	Type	Product name
807204012	Femmina	F VEP17P 1 SAE

Spare kits

Product code	Product name
815701400	SPARE KIT OR NBR+BK M VEP17

Caps

Product code	Product name
815303133	PLASTIC CAP M VEP17 BLACK
815305079	ALUMINUM CAP M VEP17 NATURAL
815300079	ALUMINUM CAP M VEP17 RED*
815301079	ALUMINUM CAP M VEP17 YELLOW*
815302079	ALUMINUM CAP M VEP17 BLUE*
815303079	ALUMINUM CAP M VEP17 BLACK*
815304079	ALUMINUM CAP M VEP17 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service