
# M VEP30P 1-1/2 SAE

Codice articolo: **807204017** / **Male**




| | |
|---|---|
| **Valving style**<br>Flat face | **Body size**<br>1-1/2" |
| **Sealing**<br>Nitrile NBR | **Treatment**<br>Cr3 + QPQ |
| **Interchange**<br>Stucchi profile VEP | **Connection system**<br>Screw |
| **Disconnection system**<br>Unscrew | **Material**<br>Carbon steel |
| **Locking mechanism**<br>Screw to connect | **Disconnectable under pressure**<br>Yes |
| **Thread**<br>FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1) | **Connectable under residual pressure**<br>Pressure in both sides |
| **Temperature**<br>-20 / +100 °C; -4 / +212 °F | **Applications**<br>Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Steel Mill, Die Casting, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas |

| Performance | IMPERIAL |
|---|---|
| Max. Flow suggested (gpm) | 198.75 |
| Max. Operating pressure - coupled (psi) | 5800 |
| Operating pressure - uncoupled (psi) | 5800 |
| Burst pressure - coupled (psi) | 15950 |
| Burst pressure - uncoupled (psi) | 15950 |
| Spillage (ml) | 0.2 |
| Manual connect torque (lbf ft) | 19.162 |
| Manual disconnect torque (lbf ft) | 9.2125 |
| Tightening torque (lbf ft) | 114,24-128,98 |

| Dimensions | IMPERIAL |
|---|---|
| Port (A) | 1-7/8-12UN |
| Overall length M+F (in) | 10 |
| Length (in) | 5,91 |
| Max. diameter (in) | 3,54 |

## Related products

| Product code | Type | Product name |
|---|---|---|
| 807204016 | Femmina | F VEP30P 1-1/2 SAE |

## Spare kits

| Product code | Product name |
|---|---|
| 815700741 | SPARE KIT OR NBR+OR HOLDER M VEP30 |

## Caps

| Product code | Product name |
|---|---|
| 815303137 | PLASTIC CAP M VEP30 BLACK |
| 815305083 | ALUMINUM CAP M VEP30 NATURAL |
| 815300083 | ALUMINUM CAP M VEP30 RED* |
| 815301083 | ALUMINUM CAP M VEP30 YELLOW* |
| 815302083 | ALUMINUM CAP M VEP30 BLUE* |
| 815303083 | ALUMINUM CAP M VEP30 BLACK* |
| 815304083 | ALUMINUM CAP M VEP30 GREEN* |

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service