
M VP21P 1 BSP

Codice articolo: **807300023** / **Male**



Valving style Flat face	**Body size** 1"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect + Safety sleeve	**Disconnectable under pressure** Yes
Thread FEMALE THREAD BSPP (ISO 1179-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	100.17
Max. Operating pressure - coupled (psi)	6815
Operating pressure - uncoupled (psi)	6815
Burst pressure - coupled (psi)	17400
Burst pressure - uncoupled (psi)	17400
Spillage (ml)	0.06
Manual connect torque (lbf ft)	1.6214
Manual disconnect torque (lbf ft)	2.3584
Max. residual pressure during connection (in the male, female to drain) (psi)	3625
Max. residual pressure during connection (in the female, male to drain) (psi)	3625
Max. residual pressure during connection (in male and female) (psi)	2175
Max. residual pressure during disconnection (psi)	2175

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	8,42
Length (in)	5,39
Max. diameter (in)	2,99
Weight (lb)	5,84

Related products

Product code	Type	Product name
807300022	Femmina	F VP21P 1 BSP

Spare kits

Product code	Product name
815700345	SPARE KIT OR NBR+BK M FF 100

Caps

Product code	Product name
815305061	ALUMINUM PLUG M VP21 NATURAL
815300061	ALUMINUM PLUG M VP21 RED *
815301061	ALUMINUM PLUG M VP21 YELLOW *
815302061	ALUMINUM PLUG M VP21 BLUE *
815303061	ALUMINUM PLUG M VP21 BLACK *
815304061	ALUMINUM PLUG M VP21 GREEN *

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service