
M VP17P 1 SAE

Codice articolo: **807304013** / **Male**



Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect + Safety sleeve	**Disconnectable under pressure** Yes
Thread FEMALE THREAD SAE (ISO 11926-1 & SAE J1926-1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	METRIC
Max. Flow suggested (l/min)	200
Max. Operating pressure - coupled (MPa)	50
Operating pressure - uncoupled (MPa)	50
Burst pressure - coupled (MPa)	125
Burst pressure - uncoupled (MPa)	125
Spillage (ml)	0.01
Manual connect torque (Nm)	2
Manual disconnect torque (Nm)	1.4
Max. residual pressure during connection (in the male, female to drain) (Mpa)	25
Max. residual pressure during connection (in the female, male to drain) (Mpa)	25
Max. residual pressure during connection (in male and female) (Mpa)	15
Max. residual pressure during disconnection (Mpa)	15

Dimensions	METRIC
Port (A)	1-5/16-12UN
Overall length M+F (mm)	202,5
Length (mm)	127,1
Max. diameter (mm)	60
Weight (kg)	1,58

Related products

Product code	Type	Product name
807304012	Femmina	F VP17P 1 SAE

Spare kits

Product code	Product name
815700655	SPARE KIT OR NBR+BK M FF 34

Caps

Product code	Product name
815305059	ALUMINUM PLUG M VP17 NATURAL
815300059	ALUMINUM PLUG M VP17 RED*
815301059	ALUMINUM PLUG M VP17 YELLOW*
815302059	ALUMINUM PLUG M VP17 BLUE*
815303059	ALUMINUM PLUG M VP17 BLACK*
815304059	ALUMINUM PLUG M VP17 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service