M VEP17HD 1 NP

Codice articolo: **808101013** / **Male**

Valving style Flat face	**Body size** 3/4"
Sealing Nitrile NBR	**Treatment** Cr3 + QPQ
Interchange Stucchi profile VEP	**Connection system** Screw
Disconnection system Unscrew	**Material** Carbon steel
Locking mechanism Screw to connect	**Disconnectable under pressure** Yes
Thread FEMALE THREAD NPT (ANSI B.1.20.1)	**Connectable under residual pressure** Pressure in both sides
Temperature -20 / +100 °C; -4 / +212 °F	**Applications** Construction Equipment Attachments, Demolition, Drilling Rig, Coil Tubing Unit, Earth Moving, Foundation, Material Handling, Road Construction, Utensili idraulici, Construction, Trucks & Vehicles, Oil & Gas

Performance	IMPERIAL
Max. Flow suggested (gpm)	5.3
Max. Operating pressure - coupled (psi)	7250
Operating pressure - uncoupled (psi)	7250
Burst pressure - coupled (psi)	18125
Burst pressure - uncoupled (psi)	18125
Spillage (ml)	0.02
Manual connect torque (lbf ft)	4.1272
Manual disconnect torque (lbf ft)	2.6532
Tightening torque (lbf ft)	81,07-95,81
Max. residual pressure during connection (in the male, female to drain) (psi)	3625
Max. residual pressure during connection (in the female, male to drain) (psi)	3625
Max. residual pressure during connection (in male and female) (psi)	2175
Max. residual pressure during disconnection (psi)	2175

Dimensions	IMPERIAL
Port (A)	1"
Overall length M+F (in)	7,91
Length (in)	4,88
Max. diameter (in)	2,31
Weight (lb)	2,92

Spare kits

Product code	Product name
815701400	SPARE KIT OR NBR+BK M VEP17

Caps

Product code	Product name
815303133	PLASTIC CAP M VEP17 BLACK
815305079	ALUMINUM CAP M VEP17 NATURAL
815300079	ALUMINUM CAP M VEP17 RED*
815301079	ALUMINUM CAP M VEP17 YELLOW*
815302079	ALUMINUM CAP M VEP17 BLUE*
815303079	ALUMINUM CAP M VEP17 BLACK*
815304079	ALUMINUM CAP M VEP17 GREEN*

**Product available upon request*

STUCCHI Quick Couplings Catalog - April 2021 - All right reserved.
Via della Lira Italiana, 397 24040 - Pagazzano (BG) Italy - Contact us
Texts, data and illustrations mentioned in this catalogue may be changed by Stucchi at any time, without notice; always refer to the version uploaded on the English version of stucchigroup.com/en website for the latest release. In case of doubt, please contact Stucchi technical service